



Immersion Thermostat P5686

Order code: P5686

THE MOST IMPORTANT PARAMETERS

Parameter	Value
type of control	manual thermostat
thermostat type	wire, flow thermostat
control mode	heating and cooling system
temperature adjustment	from 5 °C up to 80 °C, after 0.1 °C

OTHER PARAMETERS

Parameter	Value
temperature adjustment type	manually
adjustable variance of temperature	from 0.1 °C up to 15 °C, after 0.1 °C
temperature measurement	5 °C to 80 °C, resolution 0.1 °C
capillary sensor length	not stated
number of programs	not stated
ON/OFF function	yes
backlight display	yes
colour	white
switching	voltage 230 V AC, 50 Hz
range in open space	not stated
anti-frost protection	no
power of receiver	not stated
holiday mode	no
Set-back function	not stated
power source	230 V AC
possibility to connect to other detectors	not stated
power of gateway	not stated
power of transmitter	not stated
operating frequency	not stated
part of the package	not stated
switching load	5 A resistively, 1.5 A inductively
temperature calibration	no
supported OS	#
compatibility	#

protocol	-
transmission frequency	#
control by voice assistants	#
notifications to the mobile app	#
aplication languages	#
receiver's dimension	not stated
gateway's dimension	not stated
dimensions	45 x 36 x 140 mm, thermowell: 58 mm, Ø 8 mm, 1/2" thread
transmitter's dimension	not stated
packaging	1 pc, small box

www.tomita.lt